

## REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE

5/5/97

3. REPORT TYPE AND DATES COVERED

Final 15 Dec 94 - 14 Dec 96

4. TITLE AND SUBTITLE

DURIP-94: PHASE CONJUGATE INJECTION LOCKING OF LASER DIODE ARRAYS

5. FUNDING NUMBERS

61103D

3484/US

6. AUTHOR(S)

Jack Feinberg

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

University of Southern California  
Dept. of Physics  
Los Angeles, CA 90089-0484

AFOSR-TR-97

ON

0175

8. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

AFOSR/NE  
110 Duncan Avenue Suite B115  
Bolling AFB DC 20332-8050

10. SPONSORING/MONITORING AGENCY REPORT NUMBER

F49620-95-1-0103

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release: distribution unlimited

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

This is an "equipment only" grant under the Defense University Research Instrumentation Program. A report of the results obtained with this equipment is contained in the final report for Grant F49620-95-1-0082, "Phase-Conjugate Injection Locking of Laser Diode Arrays." To avoid duplication of paperwork, only a partial summary of that report will be duplicated here. This grant is to produce high-brightness, narrow-frequency light beams from semiconductor laser arrays using optical phase conjugation. The investigators recently demonstrated that their proposed techniques are both practical and efficient, and can be applied to commercially available semiconductor lasers. Their experiments coupled an optical phase conjugator to a broad-area semiconductor laser, causing the laser to emit a 0.5 watt, near-diffraction-limited output beam. Their system is simple and compact, and it also automatically adjusts for any frequency drift or gradual misalignment of the optical components. The investigators extended their techniques from single, broad-area lasers to powerful semiconductor laser arrays.

14. SUBJECT TERMS

Lasers, phase conjugation

15. NUMBER OF PAGES

4

16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT

Unclassified

18. SECURITY CLASSIFICATION OF THIS PAGE

Unclassified

19. SECURITY CLASSIFICATION OF ABSTRACT

Unclassified

20. LIMITATION OF ABSTRACT

UL

page 1

**Final Report**

submitted to the  
Air Force Office of Scientific Research  
Bolling AFB, Building 410,  
Washington, D.C. 20332-6448

**ATTN.: Dr. Howard Schlossberg**

- 1) Date submitted: MAY 4, 1997
- 2) Title: DURIP-94: PHASE CONJUGATE INJECTION LOCKING OF LASER DIODE ARRAYS
- 3) Principal Investigator: JACK FEINBERG, DEPARTMENT OF PHYSICS  
Office: (213) 740-1134, Fax: (213) 740-6653
- 4) Time period covered: DECEMBER 15, 1994 - DECEMBER 15, 1996
- 5) Institution Name: UNIVERSITY OF SOUTHERN CALIFORNIA, LOS ANGELES, CALIFORNIA  
90089-0484
- 6) Federal agency identifying award number: F49620-95-1-0103

19970602 142

page 2

**DURIP-94: PHASE CONJUGATE INJECTION LOCKING OF LASER DIODE ARRAYS**

Jack Feinberg  
Department of Physics  
University of Southern California  
Los Angeles, California 90089-0484  
(213) 740-1134 (Voice)  
(213) 740-6654 (Fax)

**A) Summary of Overall Progress:**

This goal of this project was to produce a high-brightness, narrow-frequency light beam from a semiconductor laser array. We used a mutually-pumped phase conjugator to couple a single-frequency master laser into a high-power diode laser array. This injected light narrowed the frequency bandwidth of the laser array's output beam. Tuning the master laser (by adjusting its current or its temperature) then smoothly tuned the laser array, while the output beam remained diffraction limited. We characterized and optimizing the mutually-pumped phase conjugator, which is the key element for aiming light from the injecting laser into the numerous lasers making up the laser array. We compared the performance of the four types of mutually-pumped phase conjugators for injecting light into a laser array. We have also pursued a number of other, related projects. In particular, we have published new results on the following:

- 1) We developed a new technique for detecting domains hidden in photorefractive crystals. These  $180^\circ$  domains are usually not wanted, for they diminish the efficiency of beam-coupling in such crystals. Our simple technique maps the location of any  $180^\circ$  domains in three dimensions.
- 2) We measured the phase of the light produced by frequency doubling in a self-phase matched optical fiber.
- 3) We measured the anisotropy of the mobility of holes in barium titanate crystals. We show that the drift mobility perpendicular to the crystal's c-axis is 40 times that along the c-axis.

**B) Accomplishments/New Findings**

See below and final report of grant F49620-95-1-0082

**C) Current Problems or Unusual Developments:**

None.

**D) Changes from Original Proposal:**

None.

page 3

**E) Publications**

S. C. de la Cruz, S. MacCormack, J. Feinberg, Q. B. He, H. K. Liu, and P. Yeh, "Effect of beam coherence on mutually pumped phase conjugators," J. Optical Society of America-B 12, 1363-1369 (1995).

V. Grubsky, S. MacCormack, and J. Feinberg, "All-optical three-dimensional mapping of 180° domains hidden in a BaTiO<sub>3</sub> crystal," Opt. Lett. 21, 6-8 (1996).

P. Lambelet and J. Feinberg, "Phase of second-harmonic light self-generated in a glass fiber," Opt. Lett. 21, 925-927 (1996).

D. Mahgerefteh, D. Kirillov, R. S. Cudney, G. D. Bacher, R. M. Pierce, and J. Feinberg, "Anisotropy of the hole drift mobility in barium titanate," Phys. Rev. B. 53, 7094 - 7098 (1996).

**F) Personnel Supported**  
Equipment only.**G) Interactions****Contributed talks:**

"Frequency locking of two elements of a laser diode array using mutually pumped phase conjugation," S.-C. De La Cruz, S. MacCormack, P. Lambelet and J. Feinberg, Photorefractive Materials, Effects and Devices, Estes Park, Colorado, June 11-14, 1995.

CLEO -96: "Dynamic mapping of 180° domains hidden in photorefractive crystals," Victor Grubsky, Stuart MacCormack and Jack Feinberg.

Nonlinear Optics: Materials, Fundamentals, and Applications (Maui, Hawaii): "Powerful, diffraction-limited semiconductor laser using photorefractive beam coupling," Stuart MacCormack, Jack Feinberg, Steve O'Brien, Robert J. Lang, Marvin B. Klein, Barry A. Wechsler

**Collaborations with**

1) Prof. Robert Eason  
Optoelectronics Research Centre  
University of Southampton  
Southampton, England

2) Patrick Lambelet  
Laboratoire d'Optique Appliquée  
Ecole Polytechnique Fédérale  
Lausanne, Switzerland

page 4

3) Marvin Klein and Barry Wechsler  
Hughes Research Labs  
Malibu, CA

4) Steve O'Brien and Robert Lang  
SDL, Inc.  
Santa Clara, CA

5a) Q. Byron He and 5b) Hua-Kuang Liu  
of the Jet Propulsion Laboratory,  
California Institute of Technology,

6) Pochi Yeh  
of the Department of Electrical and Computer Engineering,  
University of California at Santa Barbara.

**G) New Discoveries, Inventions, or Patent Disclosures**

A new method for detecting and mapping 180° domains hidden in photorefractive crystals. No disclosure filed.

**H) Honors or Awards**

The principal investigator, Jack Feinberg, won a nice award: the 1995 Discover Award for "Technological Innovation In The Field Of Sight." This was a national competition. An article about this work was printed in the June, 1995 issue of Discover magazine.